Data		
Vendor	White-Rodgers	
W/R Part No.	36H64-463	
Туре	Redundant - Combination	
Voltage	24 VAC	
Frequency	50/60Hz	
Current [2 stage]	.54 A	
Ambient Temp	-40°F to 175°F	
Pipe Size [NPT] vs Capacity LP	@ 1" W.C. Pressure Drop	
³ / ₄ " X ³ / ₄ "	486,000 BTUH	
Pipe Size [NPT] vs Capacity NG	@ 1" W.C. Pressure Drop	
³ ⁄ ₄ " X ³ ⁄ ₄ "	300,000 BTUH	
Pressures		
Maximum Inlet Pressure	14" W.C. or 1/2 PSI Max.	
Regulator Adj. Range, 1 Stage LP	7.0 – 12.0" W.C.	
Regulator Adj. Range, 1 Stage NG	2.5 to 5.0" W.C.	
Setting	3 ½" +/3" W.C.	
Terminations	1/4" Spade [3], 3/16" [1]	
CSA File	165039-1636373	

	REV	NOTES	DATE		
	01	Opening curve added as page 2. DGR	11/5/07		
1	Notes:				

1. Items included with gas control:

[2] NPT adapter bushings Installation instructions

кит LP Conversion instructions LP Conversion warning label [2] LP Labels [2] Springs [2]

> Field conversion instructions Lighting instruction label [self adhesive]

1/4" Spade jumper assembly [3 connections] [used for non-piloted applications]

Brass tube bushing [1]

2. See manufacturer specifications for 2 stage adjustment range.



